


### Technical Data Sheet

Article	<b>Life Recycled Nylon</b>	
Composition	<b>78% POLYAMIDE (recycled) 22% ELASTANE</b>	
Weight m <sup>2</sup> (+/- 5%)	<b>190 g/m<sup>2</sup></b>	
Weight linear m. (+/- 5%)	<b>285 g/m lin.</b>	
Total width (+/- 2%)	<b>150 cm</b>	
Dimensional Stability – Washing 40° C BS EN ISO 6330 @40°C - flat dry	width <b>-5% MAX</b>	length <b>-5% MAX</b>
Dimensional Stability – Steam	width <b>-3% MAX</b>	length <b>-3% MAX</b>
Resistance to pilling NU Martindale – ISO 12945-2 7000 rotations	on fabric <b>5</b>	on wool <b>4/5</b>
Hand Elongation (+/- 15%)	width <b>90%</b> (min 76% - max 104%)	length <b>150%</b> (min 127% - max 173%)
Stretch to Dynamometer (+/- 15%) INSTRON 3343 – load 3.6 kg - strip test - size of the tested sample: 100 mm x 50 mm		
Plain dyed	width <b>85%</b> (min 72% - max 98%)	length <b>145%</b> (min 123% - max 167%)
<i>Modulus 40%</i> Plain dyed	width <b>150-290g</b>	length <b>130-230g</b>

Care labelling codes:



Recycled Polyamide



Ultra Chlorine Resistant



Sun Creams and Oil Resistant



Muscle Control



Shape Retention



Excellent UV Protection



Excellent Coverage



Ultra Flat



Soft



Two-way Stretch



Pilling Resistant



Perfect Fit



Extra Comfort

**Notes:**

Technical Specification details prior to a print or foil application.

Please note due to the numerous different Industries we supply, we cannot perform tests to everyone's requirement therefore we strongly recommend you carry out your own tests.

We recommend testing each dyebath before any treatment or application other than cutting and sewing. To improve our products, we reserve to modify these, as and when necessary.