




Unit E, 3 Tudor Road, Altrincham Business Park, Cheshire, WA14 5RZ  
 Tel : 0161 975 9002 Email : sales@friedmans.co.uk Web : [www.friedmans.co.uk](http://www.friedmans.co.uk)


### Technical Data Sheet

Article	<b>Rib Matt</b>	
Composition	<b>92% POLYAMIDE 8% ELASTANE</b>	
Weight m <sup>2</sup> (+/- 5%)	<b>200 g/m<sup>2</sup></b>	
Weight linear m. (+/- 5%)	<b>280 g/m lin.</b>	
Total width (+/- 2%)	<b>140 cm</b>	
Dimensional Stability – Washing 40° C BS EN ISO 6330 - flat dry	width <b>-10% MAX</b>	length <b>-5% MAX</b>
Steam	width <b>-6% MAX</b>	length <b>-4% MAX</b>
Resistance to pilling NU Martindale – ISO 12945-2 7000 rotations	on fabric <b>4/5</b>	on wool <b>2/3</b>
Stretch to Dynamometer (+/- 10%) ZWICK – load 1,5 kg – strip test – size of tested sample 100mm x 50mm		
Plain dyed	width <b>145%</b> (min 131% - max 160%)	length <b>90%</b> (min 81% - max 99%)
<i>Modulus 40%</i> Plain dyed	width <b>65-115g</b>	length <b>145-270g</b>

Care labelling codes:



Pilling Resistant



Breathable



Sun Creams and Oil Resistance



Two-way Stretch



Excellent UV Protection



Excellent Coverage



Soft



Extra Comfort



Perfect Fit



Quick Drying

#### Notes:

Technical Specification details prior to a print or foil application.

Please note due to the numerous different Industries we supply, we cannot perform tests to everyone's requirement therefore we strongly recommend you carry out your own tests.

We recommend testing each dyebath before any treatment or application other than cutting and sewing. To improve our products, we reserve to modify these, as and when necessary.